

RefLED ES50


RefLED ES50 V5 425lm 830 36° SL

0027447



Product features

- Compact, energy efficient and exceptional value for money product.
- Same shape and size as halogen GU10 lamp
- Compact Cluster SMD technology enabling high efficiency with halogen look
- Reduced visible heat sink from the front
- Available in 36 degree
- High lumen efficacy
- 15,000 hours average rated life
- 3 years warranty



NOTES

undefined

PRODUCT OVERVIEW

IPC Code	0027447
Product name	RefLED ES50 V5 425lm 830 36° SL
Technology	LED
Watt (Rated) (W)	6.20
Cap/Base	GU10
Fixture rating	Open
General application	Office, Hospitality, Retail, Education, Residential & Consumer, Museums & Galleries,
ETIM Class	EC001959
E-number FI	4740469
E-number SE	8292499
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Beam Angle (°)	36
Wattage (W)	6.20
Product Voltage (V)	230
Average life (Nominal) (h)	15000

DATA TABLE

General data

IPC Code	0027447
Product name	RefLED ES50 V5 425lm 830 36° SL
Technology	LED
Watt (Rated) (W)	6.20

RefLED ES50

RefLED ES50 V5 425lm 830 36° SL

0027447

Cap/Base	GU10
Fixture rating	Open
General application	Office, Hospitality, Retail, Education, Residential & Consumer, Museums & Galleries,
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740469
E-number SE	8292499

Optical data

Rated Luminous Flux Useful (lm)	425
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Rated Luminous Intensity (cd)	960
Beam Angle (°)	36
Beam angle (Rated) (°)	36
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	6.20
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1.0
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	50000
Inrush Current (A)	3.65
Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	7
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	90
Max. Luminaires per 16A C Breaker	140
Max. Luminaires per 20A C Breaker	180

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	54
Nominal Product Diameter (mm)	50
Weight (kg)	0.038

RefLED ES50

RefLED ES50 V5 425lm 830 36° SL
0027447


Packaging

Single packaging type	Carton
Packaging single length / height (cm)	6.1
Packaging single width (cm)	5.2
Packaging single depth (cm)	5.2
DUN14 (inner)	25410288274472
Units per inner package	6
Packaging inner length / height (cm)	16.7
Packaging inner width (cm)	11.6
Packaging inner depth (cm)	7.5
DUN14 (outer)	15410288274475
Units per outer package	60
Packaging outer length / height (cm)	59.8
Packaging outer width (cm)	18.7
Packaging outer depth (cm)	17.1

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

TECHNICAL DRAWINGS



RefLED ES50

RefLED ES50 V5 425lm 830 36° SL
0027447

