



### PRODUCT FEATURES

- Perfectly designed as replacement for incandescent lamps which deliver a warm and cosy atmosphere by clear filament lamps
- RichColour (CRI $\geq$  90) applies to all dimmable lamps maximizing colour richness
- Offers perfect linear dimming which is compatible with most popular EU dimmer
- 360° light illumination with uniform light distribution and high quality lighting performance
- Ideal for decorative fixtures with filament design
- High efficacy of up to 128 lm/W
- Up to 90% instant energy savings compared to traditional light bulbs

### APPLICATIONS

- Decorative Installations
- Domestic Applications
- Hotels
- Restaurants
- Shops



## GENERAL INFORMATION

Model Number	LG9604CS
Product Code	LG9604CS+E14+827+V0240
Cap Base	E14
Dimmable	No
Warm Up Time 60% of Full Light	Instant
Starting Time	<0.5 s
Working Temperature	-30°C to +45°C
Cover Design	Clear
Flammability of Plastic Component	$\geq$ V2
Series	P45 (Filament Lamps)

## LIFE PERFORMANCE

Lifetime (L70 B50)	15000
Number of Switching Cycles	>1000000

## ELECTRICAL DATA

Input Voltage	220-240 VAC
Frequency	50 Hz
Power Factor	> 0.4
Equivalent Wattage	40 W
Power	4 W
Input Current	40 mA

## PHOTOMETRICAL INFORMATION

Luminous Flux	470 lm
Luminous Efficacy	118 lm/W
Colour Temperature	Warmwhite (2700K) K
CRI	$\geq$ Ra80
Beam Angle	360°
Flickering	$\leq$ 3% at 100Hz

## CERTIFICATES &amp; STANDARDS

Weighted Energy Consumption	4
Photobiological Safety Group	RG1
Lamp Cap Twist Safe	1.15
Approvals	CE, RoHS
Standards Compliance	IEC/EN 62560, IEC/EN 62493, IEC/EN 62471, ERP 244, IEC 62612, IEC CISPR15, EN 55015, IEC/EN 61547, IEC/EN 61000-3-2, IEC/EN 61000-3-3

#### LOGISTIC INFORMATION

MM Code	Packaging Unit	Outer Box Dimensions			Gross Weight per Outer Box
		L	W	H	
	pcs/unit	mm	mm	mm	kg
146230/ MM09900	1	48	48	90	0.0311
	60	329	266	217	2.35