



SmartBright G2 LED Floodlight

BVP151 LED200/WW 220-240V 200W AWB CE

SmartBright G2 LED Floodlight delivers high lumen efficacy, with long lifetime and reliable design. Asymmetric optical distribution improves light effect. The product is an ideal solution for most floodlight applications.

Product data

General Information	
Lamp colour code	730 warm white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	FG [Flat glass]
Control interface	-
Connection	Flying leads/wires
Cable	Cord 0.6 m without plug
Protection class IEC	Safety class I (I)
Flammability mark	NO [-]
CE mark	CE mark
Outdoor optic type	Asymmetrical
LED engine type	LED
Serviceability class	Class C, luminaire without serviceable parts, not serviceable

Light Technical

Standard tilt angle post-top	-
Standard tilt angle side entry	-

Operating and Electrical	
Input voltage	220-240 V
Input frequency	50 or 60 Hz
Power factor (min.)	0.9

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Housing material	Aluminum die-cast
Optical cover/lens material	Tempered glass
Mounting device	MBA [Mounting bracket adjustable]
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	491 mm
Overall width	378 mm
Overall height	60 mm
Colour	Dark Grey

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
-------------------------	---

SmartBright G2 LED Floodlight

Mech. impact protection code	IK08 [5 J vandal-protected]
Surge protection (common/differential)	Luminaire surge protection level up to 4 kV differential mode and 4 kV common mode

Initial Performance (IEC Compliant)


Initial luminous flux	19000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	95 lm/W
Lamp colour temperature	3000 K
Colour Rendering Index	80
Initial input power	200 W
Power consumption tolerance	+/-10%

Application Conditions


Ambient temperature range	-25 to +40 °C
----------------------------------	---------------

Product Data

Full product code	871016334362499
Order product name	BVP151 LED200/WW 220-240V 200W AWB CE
EAN/UPC – product	8710163343624
Order code	911401816580
Numerator – quantity per pack	1
Numerator – packs per outer box	2
Material no. (12NC)	911401816580
Net weight (piece)	6.080 kg



Dimensional drawing



BVP151 LED Underwater

