



PRODUCT FEATURES

- Tunable white colour changing from 3000K to 6500K and dimmable functions offer flexibility of lighting design
- Easy operation via a remote controller
- Up to 80% energy saving compared to standard incandescent light sources
- Seamless dimming from 100% to 5%
- 2 different finishings (white & chrome)
- With memory function

APPLICATIONS

- Bedrooms
- Hotels
- Living Rooms
- Lobbies
- Restaurants

GENERAL INFORMATION

Input Voltage / Frequency	220-240 VAC / 50/60
Power Factor	>0.9
Dimmability	Smart-Dim
CRI	> Ra80
Colour Consistency	<6
Lifetime	25,000hrs L70B50@Ta25°C
Number of Switching Cycles	100000
Protection Class	CL I
Glow Wire	650
Flickering percentage	<10% @100Hz
Working Temperature	-20 to +40
Material & Colour	Steel / White

PRODUCT INFORMATION

Model no.	MM Code	Power W	Luminous Flux lm	Luminous Efficacy lm/W	Power Factor (λ)
FCL73900v0-tw	711028 / MM11028	-	-	70	>0.9
FCL74000v0-tw	711030 / MM11030	-	-	72	>0.9

OPTIONAL ACCESSORIES

Model No.	MM Code	Description
-	-	Control



Control

Model no.	Inrush Current	Inrush Duration	Max. No. of Luminaire Connection on MCB			
	A	µs	B10	B16	C10	C16
FCL73900v0-tw	-	-	-	-	-	-
FCL74000v0-tw	-	-	-	-	-	-

DIMENSIONS & WEIGHT

Model no.	Ø	H	Weight
	mm	mm	g
FCL73900v0-tw	430	80	-
FCL74000v0-tw	530	81	-

LOGISTIC INFORMATION

Model no.	Packaging Unit	Outer Box Dimensions			Gross Weight per Outer Box
	pcs/unit	L mm	W mm	H mm	kg
FCL73900v0-tw		-	-	-	-
FCL74000v0-tw		-	-	-	-