



### PRODUCT FEATURES

- Tunable white and colour changing functions offer flexibility of lighting design
- Easy operation via a remote controller or app via mobile phone
- Up to 80% energy saving compared to standard incandescent light sources
- Smooth dimming from 100% to 10%
- Uniform light distribution
- Smooth surface for easy cleaning
- Night mode available
- With memory function

### APPLICATIONS

- Hotels
- Living Rooms
- Lobbies
- Restaurants

### GENERAL INFORMATION

Input Voltage / Frequency	220-240 VAC / 50/60
Power Factor	>0.9
Dimmability	Smart-Dim
CRI	> Ra80
Colour Consistency	<6
Lifetime	25,000hrs L70B50@Ta25°C
Number of Switching Cycles	100000
Protection Class	CL I
Glow Wire	650
Flickering percentage	<10% @100Hz
Working Temperature	-20 to +40
Material & Colour	Steel / White

### PRODUCT INFORMATION

Model no.	MM Code	Power W	Luminous Flux lm	Luminous Efficacy lm/W	Power Factor (λ)
FCL74100v0-wf/ec/tw	711031 / MM11031	-	-	70	>0.9

Model no.	Inrush Current	Inrush Duration	Max. No. of Luminaire Connection on MCB			
	A	μs	B10	B16	C10	C16
FCL74100v0-wf/ec/tw	-	-	-	-	-	-

### DIMENSIONS & WEIGHT

Model no.	Ø	H	Weight
	mm	mm	g
FCL74100v0-wf/ec/tw	555	73	-

### LOGISTIC INFORMATION

Model no.	Packaging Unit	Outer Box Dimensions			Gross Weight per Outer Box
		L mm	W mm	H mm	
FCL74100v0-wf/ec/tw	pcs/unit	-	-	-	kg