

PRODUCT FEATURES

- Perfectly designed as replacement for incandescent lamps which deliver a warm and cosy atmosphere by clear filament lamps
- Offers perfect linear dimming which is compatible with most popular EU dimmers
- 360° light illumination with uniform light distribution and high quality lighting performance
- Ideal for decorative fixtures with filament design
- Flicker Free ≤ 3% for non-dimmable lamps
- High efficacy of up to 211 lm/W
- Up to 94% instant energy savings compared to traditional light bulbs

APPLICATIONS

- Decorative
 Installations
- Dining Rooms
- Hotels
- Residential lighting
- Restaurants



GENERAL INFORMATION

Model Number	LG9804CS
Product Code	LG9804CS+E27+827+V0240
Cap Base	E27
Dimmable	No
Warm Up Time 60% of Full Light	Instant
Starting Time	< 0.5 s
Working Temperature	-30°C to +45°C
Cover Design	Clear
Series	A60 (Filament Lamps)

LIFE PERFORMANCE

Lifetime (L70 B50)	50000
Number of Switching Cycles	> 100000

ELECTRICAL DATA

Input Voltage	220-240 VAC
Frequency	50 Hz
Power Factor	≥ 0.40
Displacement Factor	0.40
Equivalent Wattage	62 W
Power	4 W
Input Current	42 mA
Surge Protection	500

PHOTOMETRICAL INFORMATION

Luminous Flux	840 lm
Luminous Efficacy	210 lm/W
Colour Temperature	2700 K
Colour Consistency	6
CRI	Ra80
Flickering	≤ 3% at 100Hz
SVM	0.4
Pst LM	1.0
Chromaticity Coordinates (x and y)	0.458, 0.410

CERTIFICATES & STANDARDS

Weighted Energy Consumption	4
Energy Class	A
Photobiological Safety Group	RG1

www.megaman.cc info@megaman.cc © Copyright 2023. All rights reserved by MEGAMAN°

A60

Filament Lamps


MEGAMAN[®]

PRODUCT DATASHEET

LG9804CS+E27+827+V0	0240
---------------------	------

Lamp Cap Twist Safe	3
Approvals	CE, RoHS
Standards Compliance	IEC/EN 62560, IEC/EN 62493, IEC/EN 62471, ErP 2019/2020, IEC 62612, IEC CISPR15, EN 55015, IEC/EN 61547, IEC/EN 61000-3-2, IEC/EN 61000-3-3

DIMENSIONS & WEIGHT



Width (W)	60 mm
Height (H)	104 mm
Diameter (D)	60 mm
Weight	31.4 g

LOGISTIC INFORMATION

MM Code	Packaging Unit	Outer Box Dimensions		sions	Gross Weight per Outer Box
		L	W	Н	
	pcs/unit	mm	mm	mm	kg
-	1	70	70	120	0.056
	60	457	376	278	4.08