#### PRODUCT DATASHEET

LS202078/dm-CSv00+E27+827+V0240



#### **PRODUCT FEATURES**

- MEGAMAN® LED Crown Silver with the unique silver-plated crown top and clear light bulb finishing
- Crown Silver is best for flawless mirror lighting and decorative lighting with an aesthetic touch, it delivers non-glare lighting just like an incandescent lamp with silver coating
- High efficacy of up to 105 lm/W
- Up to 88% instant energy savings compared to traditional light bulbs

#### **APPLICATIONS**

- Lounges
- Reception Areas
- Restaurants
- Showrooms
- Wall Lighting



# **Crown Silver**

#### Decorative

LS202078/dm-CSv00+E27+827+V0240



#### PRODUCT DATASHEET

63W/7.8W E27 860lm 2700K Ra80 Dimmable

#### **GENERAL INFORMATION**

Model Number	LS202078/dm-CSv00
Product Code	LS202078/dm-CSv00+E27+827+V0240
Cap Base	E27
Dimmable	100-5%
Warm Up Time 60% of Full Light	Instant
Starting Time	< 0.5 s
Working Temperature	-30°C to +45°C
Cover Design	Clear & Silver
Flammability of Plastic Component	≥ V2
Series	Crown Silver

#### LIFE PERFORMANCE

Lifetime (L70 B50)	15000
Number of Switching Cycles	> 100000

# **ELECTRICAL DATA**

Input Voltage	220-240 VAC
Frequency	50 Hz
Power Factor	≥ 0.80
Displacement Factor	0.80
Equivalent Wattage	63 W
Power	7.8 W
Input Current	45 mA
Surge Protection	500

#### PHOTOMETRICAL INFORMATION

Luminous Flux	860 lm
Luminous Efficacy	110 lm/W
Colour Temperature	2700 K
Colour Consistency	6
CRI	Ra80
Flickering	≤ 8% at 100Hz
SVM	0.4
Pst LM	1.0
Chromaticity Coordinates (x and y)	0.458, 0.410

#### **CERTIFICATES & STANDARDS**

Weighted Energy Consumption	8
Energy Class	Е

# **Crown Silver**

# Decorative

LS202078/dm-CSv00+E27+827+V0240




PRODUCT DATASHEET

63W/7.8W E27 860lm 2700K Ra80 Dimmable

Photobiological Safety Group	RG0
Lamp Cap Twist Safe	3
Approvals	CE, RoHS
Standards Compliance	IEC/EN 62560, IEC/EN 62493, IEC/EN 62471, ErP 2019/2020, IEC 62612, IEC CISPR15, EN 55015, IEC/EN 61547, IEC/EN 61000-3-2, IEC/EN 61000-3-3

# **DIMENSIONS & WEIGHT**



Width (W)	60 mm
Height (H)	104 mm
Diameter (D)	60 mm
Weight	34 g