

PRODUCT DATASHEET

Model: LXD115

Category: LED Recessed Linear Downlight

Description: 30w LED Recessed Linear Downlight with 0-10V Dimming



General Information

Material: Aluminum + Ferrum

Fitting Colors: Matte White/ Black

Rotation Angle (degree): Not Applicable

Tilting Angle (degree): Not Applicable

Track System: Not Applicable

IP Rating: 20

Working Temperature (°C): -20 - +32

Storage Temperature (°C): -20 - +50



Product Dimensions and Cut-out Information


Fitting Length (mm): Not Applicable

Diameter (mm): 413 x 45

Height (mm): 49

Cut-out Dimension (mm): 403 x 32

Dimension:



Packing Information

Packaging Type: Individual box

Quantity per carton: 15

CBM per carton: 0.035

Gross weight per carton (kgs): 13.9



Lifespan

Lifetime (hours): 50000

Luminous Flux after 50000hours (lm): LM80 Comply

PRODUCT DATASHEET

Model: LXD115

Category: LED Recessed Linear Downlight

Description: 30w LED Recessed Linear Downlight with 0-10V Dimming



Light Technical Information

Color Temperature	CRI (Ra)	Gamut Index (GAI)	LED Lumen	Lumen per Watt
2700	95	100	2925	72
3000	95	100	3135	78
4000	95	100	3376	90

LED Manufacturer: Luminus

LED Type: SMD

LED Model: SST-20

Optic: Reflector

Beam Angle (°): 15/30/45

Electrical Information

System Power (w): 34

Input Voltage (v) & Frequency: 100-277V 50/60Hz

Output Voltage (v): 28-30

Current (mA): 700

0-10V Dimming: RiO 700mA

Power Factor: 0.90

Efficiency (%): 81

Total Harmonic Distortion (%): <20

Dimmable: Triac Dimming – Upon Request

Dali Dimming – Upon Request